

CONDITII TEHNICE DE CALITATE
PACURA MAX. 1% SULF, FT cf. ST 14 / 2003

Utilizare:

COMBUSTIBIL ÎN FOCARELE UTILAJELOR SI INSTALATIILOR INDUSTRIALE

CARACTERISTICI		CONDITII TEHNICE DE CALITATE		Metode de analiza		
		Pacura max.1% sulf		STAS	ISO	ASTM
		usoara	greă			
Vascozitate, - la 80 °C, °E, mm ² /s	min	8	15	117-87	3104	D 445 / 96
	max	59	115			
Densitate -20 °C, g/cm ³	max	1.015		35-81	3675	D 1298 /85
Punct de congelare, °C	max	25	25	39-80		D 97 / 96
Punct de inflamabilitate M., °C	min	90	110	5489-80		D 92 /97
Aciditate minerala si alcalinitate		lipsa		22-64		D 664 /95
Apa si impuritati, %	max	1	1	24/2-89	3733	D 95 /83
Sulf, %	max	1	1	SRISO 8754/96	8754	D 4294 /90
Cenusa, %	max	0.1	0,14	38-81	6245	D 482 / 95
Putere calorifica inferioara, MJ/ kg	min	40.2	39.8	5269-82	-	D4809